

Integra



Features:

- 2 Door Access Control Panels
- Mounted on a 19" Rackmount Plate
- Multi-swipe Functionality
- Distributive Processing, Built in Clock
- Connect via Serial Port, USB or Ethernet
- Flash Upgradeable Firmware
- 3,000 Cardholders & Access Levels
- 5 Card Formats per Panel Simultaneously
- Automation Links, Anti-Passback, Etc...
- Easy to use Cardholder Database
- Comprehensive Reports

Included in RBH-URC-2003-FR360N kit:

- (2) Door Panels (Internet/LAN ready)
- (4) Supervised Programmable Inputs
- (4) Programmable Outputs
- (2) Proximity Readers (Range 3-5")
- (64) Door Software (Unlimited Sites)
- (10) Full Function Client Licenses

Compatible Software Modules:

- RBH-IRC-BB Integrated PhotoID Module
- RBH-IRC-BIO Fully Integrated Biometric Fingerprint Module
- RBH-IRC-VM Visitor Management
- RBH-IRC-CCTV DVR Integration Suite
- RBH-IRC-DT Database Transfer Wizard
- RBH-IRC-WEB Web Client

Compatible Panels:

- RBH-IRC-2000 2-Door Controllers
- RBH-URC-2004 4-Door Controllers
- RBH-URC-2002 2-Door Controllers for 19" Rack
- RBH-URC-2005 4-Door Controllers for 19" Rack
- RBH-URC-2008 Elevator Controller

RBH-URC-2003-FR360N Kit 2 Door Rack Mountable Kits With Proximity Readers

Networks per PC	32 (TCP/IP Ethernet or RS-485, supervised)
Controllers per Network	16
Communication Between Controllers:	Supervised RS-485
Speed	Programmable 9.6 - 56 Kbps
Distance	4,000 ft (1,200m)
Cable Type	18AWG, 2 conductor, twisted, shielded
Cards per Panel	3,000 (up to ten digit card numbers)
Access Levels per Panel	3,000 (one per card per panel)
Site Codes per Panel	10 (site code programming is not mandatory)
Offline Transactions Buffer	3,000 FIFO, command and alarm priority
Access Points (Readers / Keypads):	2 (Red, Green LED and Buzzer control)
Distance	Max 500ft (150m)
Cable Type	20-22 AWG, 6 or 8 conductor, shielded
Simultaneous Card Formats per Panel	5, Wiegand or Clock & Data
Programmable Supervised Inputs:	4
Input Supervision	Four state monitoring (1 or 2 resistors)
Distance	Max 1,000ft (300m)
Cable Type	20-22 AWG, 2 conductor
Programmable Outputs:	2 SPDT 5A @ 30 VDC, dry contacts 2 Electronic drivers, 12 VDC max, 100 mA
Output Mode	Programmable Fail Safe/ Fail Secure
Enclosure Size and Weight	W/L/H 12" x 14" x 3.25", Kit with readers 12 lbs
Power Requirements	12VDC 2A Liner Power Supply (not included)
Recommended Back-up Battery	12V, 7AH lead, acid or gel cell (not included)
Certifications	FC CE

*Specifications are subject to change without notice.

Also Available without readers P/N: RBH-URC-2003



WWW.RBH-ACCESS.COM

© RBH Access Technologies, Inc. 2016